



- . Compatibile con DVB-T and MPEG-2 Standard
- . Telecomando
- . Guida Programmi TV
- . 7MHz & 8Mhz software setting
- . PAL & NTSC
- . Televideo
- . 2 Scart
- . Autoscan 1gg/7gg/30gg

- . Aggiornamento SW OTA

Video Decoder

Profile level: MPEG-2 Main profile
 Input Rate: MPEG2 video decoding
 Video resolution: 720x576 pixels for PAL
 Aspect Ratio: 4:3, 16:9

Tuner

Front End: DVB-T(Silicon tuner on board)
 Input Frequency Range: 170~866MHz
 RF input Signal Level: -80 ~ -5 dBm
 RF Loop through function

System and Memory

Main Processor: CHEERTEK 216T
 Flash Memory: 8 Mbits
 SDRAM: 4Mx16Mbits

- . DGTVi compliant
- . Eup compliant
- . Multilingua
- . Ricerca Automatica & Manuale
- . 1000 canali
- . Local Channel Number
- . USB support JPEG/MP3 playback

Demodulator:

Demodulation: QPSK/16QAM/64QAM
 OFDM Spectrum: 2K and 8K

General Data:

Input Voltage range: 90 VAC ~ 240VAC (external SMPS 5V)
 Power Consumption: max 6W
 Stand-by mode: 1W
 Size (WxHxD) in mm:
 Weight:

Accessories :Quick start guide, remote control .

Connectors:

Antenna Input: IEC Female
 RF Output: IEC Male
 Two Scart: TV-VCR
 SPDIF: Coaxial Output

SOLO PER TELEVISIONE DIGITALE GRATUITA



www.telewire.it info@telewire.it

Tel +39 035 4241411 Fax +39 035 4241412